

Self-assembly is the most promising low-cost and high-throughput methodology for nanofabrication. This paper reports the optimization of a self-assembly process at room temperature for the growth of copper oxide (CuO) based nanostructures over a copper substrate using aqueous potassium hydroxide (KOH) solution as the oxidizing agent. The monoclinic ...

As revealed in Fig. 10a, the decreased arcs indicate that, with the formation of CuO transition layer, the interface charge carrier transferring exhibits an obvious improving and obtains the optimal value at Cu<sub>2</sub>O/SnO<sub>2</sub>-CuO-3, which corresponds the photovoltaic performance and indicate the CuO transition layer can accelerate the charge carrier ...

TiO<sub>2</sub>/CuO/Cu<sub>2</sub>O Photovoltaic Nanostructures Prepared by DC Reactive Magnetron Sputtering. Mariusz Bester. *Nanomaterials*. In this study, titanium dioxide/copper oxide thin-film solar cells were prepared using the reactive direct-current magnetron sputtering technique. The influence of the deposition time of the top Cu contact layer on the ...

In only 120 min of exposure to visible light, 79% of the tetracycline was degraded via Z-scheme charge transfer of Cu@CuO@MoS<sub>2</sub> core-shell 17. In the photovoltaic aspects, MoS<sub>2</sub>, NiO, and CuO have ...

In the current study, Zn-incorporated CuO (CuO:Zn) and pure CuO thin film heterojunction devices have been fabricated on n-Si (  $\approx 100 \mu\text{m}$  ) substrate, applying vapor-liquid-solid (VLS), for their potential application as photovoltaic devices. The uniformity of the thin films on Si-substrate and their crystalline orientation are verified using ...

This study explores the enhancement of cupric oxide (CuO) thin films for photovoltaic applications through chromium doping and subsequent annealing. Thin films of CuO were deposited on silicon and ...

CuO is a secondary copper mineral, a rare earth metal, and the most stable form of oxidized copper. ... The solar cell CuO(450nm)/C/ (eva.) showed a similar photovoltaic performance. This table can be found from reference 4. At Chiang Mai University, ZnO dye-sensitized solar cells (DSSCs) with different photoelectrodes were studied on the effect ...

On the other hand, there still are few works on this material yet, and the efficiencies of photovoltaic devices using CuO are still low: Kidowaki et al. [33] have developed a CuO/C 60 structure which provided power conversion efficiency of  $1.8 \times 10^{-6}\%$ ; Masudy-Panah et al. [32] developed a p-CuO:Al/n-Si heterojunction solar cell with 2% ...

TiO<sub>2</sub>/CuO/Cu<sub>2</sub>O Photovoltaic Nanostructures Prepared by DC Reactive Magnetron Sputtering. Lyubomyr

Nykyruy. Nanomaterials. In this study, titanium dioxide/copper oxide thin-film solar cells were prepared using the reactive direct-current magnetron sputtering technique. The influence of the deposition time of the top Cu contact layer on the ...

Highlights PZT/CuO composite films are prepared using sol-gel method The photocurrent is increased when PZT is combined with CuO The transport mechanism of the photoelectrons in PZT/CuO composite films is explored Keywords Photovoltaic effect Ferroelectric thin film PZT CuO 1 Introduction In the past several decades, ferroelectric materials have been

It is found that the PZT/CuO films show a short circuit photocurrent density ( $J_{SC}$ ) enhanced by nearly 6 times and power conversion efficiency (PCE) increased by six-fold when compared to those of the PZT film. The increase of photovoltaic response is due to the internal electric field of PZT/CuO p-n junction which plays an important role in driving the ...

In the last few decades, cupric oxide (CuO)-based thin films have gained a lot of attention as a photovoltaic material due to its unique structural and optoelectronic properties along with its stable monoclinic phase at room temperature [1,2,3]. CuO (a II-VI p-type semiconductor) has superior potentiality for photo-detection and optical switching applications in visible or near ...

Copper oxide (CuO) is a semiconductor material which many application for fabrication of photovoltaic solar cells [8]. The features of copper oxide semiconductors are high optical absorption and nontoxic and low cost fabrication [9]. ... Conclusions The CuO films were successfully prepared by sol-gel method with number of layers variation. CuO ...

Cupric oxide (CuO) is also used as HTL with heterostructure ZnO/CdS/CdTe/CuO having efficiency of 15% and 18% with and without defects, respectively [6]. From the above studies, it can be ...

In this research paper, the authors report a comparative study on the photovoltaic characteristics of Al/CuO/ $\alpha$ -Fe<sub>2</sub>O<sub>3</sub>:Al/ZnO:Al/SnO<sub>2</sub>:F and Al/CuO/ $\alpha$ -Fe<sub>2</sub>O<sub>3</sub>:Al/ZnO:Sn/SnO<sub>2</sub>:F solar cells by employing simple low-cost chemical spray pyrolysis (CSP) and thermal evaporation techniques. Thin films were characterized through X-ray ...

The main goal of the study is to increase the photovoltaic (PV) panel's efficiency by applying the two-phase closed thermosyphon system having CuO nanofluid, which is a heat pipe-supported passive cooling method, to photovoltaic (PV) panels. For this purpose, in addition to the selected reference panel (PV1), five different passive cooling designs were performed, and ...

In this study, the effect of CuO/EG nanofluid was investigated on the thermohydraulic performance of a photovoltaic thermal system at different Reynolds numbers. It was found that the overall Nusselt number increases by 21% at ...

-1.0 V. The photovoltaic performance for the Cu<sub>2</sub>O/CuO bilayer fabricated at -0.4 V was ameliorated by heating at 423 K, and the maximum EQE values were enhanced to 87.7% at 550 nm and 89.8% at 530 nm in an ambient atmosphere and vacuum. Both the Cu<sub>2</sub>O and CuO layers acted as photovoltaic layers in the Cu<sub>2</sub>

Copper oxide (CuO<sub>x</sub>) thin films were produced by spin-coating and electrodeposition methods, and their microstructures and photovoltaic properties were investigated. Thin film solar cells based on the Cu<sub>2</sub>O/C<sub>60</sub> and CuO/C<sub>60</sub> heterojunction or bulk heterojunction structures were fabricated on F-doped or In-doped SnO<sub>2</sub>, which showed ...

The experimentally obtained photovoltaic parameters of the p-CuO/n-Si heterojunction solar cell are compared with that of the simulation results using SCAPS 1D analysis. An open circuit voltage ...

All samples have the potential to exhibit photovoltaic properties and self-powered capabilities. Furthermore, the I-V curve confirms that the photocurrent mechanism of these junctions adheres to the recombination standard, in addition to demonstrating correction behavior. ... A sample with a CuO concentration of 0.1 M shows the highest ...

This CuO-based solar cells offer advantages due to their low cost, earth-abundant material, and potential for efficient charge transport, making them promising for scalable and ...

In recent years, metal oxide-semiconductor heterojunctions are gaining interest in fundamental photovoltaic research. This work focuses on the synthesis and characterization of ...

After coating atomic layer deposition (ALD) layers and hydrogen evolution reaction (HER) catalyst, the photocurrent density at 0 V (versus RHE) of the semitransparent Cu<sub>2</sub>O photocathode with CuO as the back layer for photoelectrochemical (PEC) water splitting reached -4.9 mA/cm<sup>2</sup>, which showed a 24.5% improvement compared with FTO/Au/Cu<sub>2</sub>O ...

In particular, CuO/CdS heterojunctions can be used in photosensing and photovoltaic devices, the latter of which addresses growing global energy demands. Metal chalcogenide materials such as PbS, ZnS, CdS, CdSe, PbSe, ZnSe, and ZnTe have attractive properties for various optoelectronic applications.

In this paper, Spray pyrolysis will be used to produce CuO thin films because it's simple and low cost method, aiming to study the impact of thin film thickness on optical, structural and electrical properties of CuO thin films for ...

EVERGREEN Joint Journal of Novel Carbon Resource Sciences & Green Asia Strategy, Vol. 11, Issue 03, pp2342-2350, September 2024 The Impact of CuO Nanofluid Volume Fraction on Photovoltaic-Thermal Collector (PV/T) Performance . Zainal Arifin<sup>1,\*</sup>, Muhammad Fuadi Hakimi<sup>1</sup>, Syamsul Hadi<sup>1</sup>, Singgih Dwi Prasetyo<sup>1,2</sup>, Watuhumalang Bhre Bangun<sup>1</sup> <sup>1</sup>Department of ...

Cupric oxide (CuO) thin films prepared by reactive d.c. magnetron sputtering technique for photovoltaic application. Author links open overlay panel S. Dolai a, ... Effect of bath concentration on the growth and photovoltaic response of SILAR-deposited CuO thin films. Appl. Phys. A, 120 (2015), pp. 1105-1111.

The novelty in the preparation of nanostructured cuprous oxide as an absorber layer for photovoltaic applications lies in the synergistic combination of tailored nanostructure design, advanced deposition techniques, enhanced ...

The photovoltaic parameters of FTO/ZnO-CuO/Al heterostructure SC like efficiency  $\eta$ , current density  $J_{sc}$  and fill factor also decreased conspicuously, whereas the open circuit voltage was found ...

Photovoltaic cells mainly absorb the solar spectrum between 700 ... Sharma et al. [24] prepared NePCMs by mixing 0.5% mass fraction of CuO in RT24 which was taken as a base PCM at 60  $\pm$  176;C and the mixture was then ultrasonicated for 24hr in an ultrasonicator machine. Show abstract. Phase change materials (PCMs) play a prime role in the ...

In the present study, CuO:ZnO nanocomposite (NC)-based heterojunction photovoltaic devices have been successfully fabricated on n-type Si ( $\approx$ 100 $\mu$ m) wafers, utilizing a simple and cost-efficient chemical bath deposition (CBD) method. The primary focus of our research was to explore the optimal weight percentage of the co-deposited CuO and ZnO in ...

Web: <https://ekusenitours.co.za>